

Dow Roofing Systems *Color Membranes*




High Performance Roofing Membrane and a wide selection of color

Stevens EP™ brand of TPO gives you a durable, versatile roofing solution you can count on for years, tested and proven in more than a decade of real-world conditions.

Stevens EP is available in a wide selection of standard colors as well as custom colors. Colored Stevens EP membrane is reinforced and available in .045- (Light Slate Gray and Buckskin only) and .060-in. (1.14 and 1.52 mm) thickness. Unreinforced .055-in. (1.4 mm) membrane is available in all colors for flashing details. The colors shown below are printer reproductions and may vary from actual membrane samples supplied. Colored membrane samples are available on request. Call 800/621-Roof ext. 1004.



ROOFING SYSTEMS



Light Slate Gray



Pewter



Buckskin



Terra Cotta



Desert Brown



Patina



Dark Ivy Green



Neon Blue

▶ **Stevens EV™ (Elvaloy® HP) and Stevens CSPE Roofing Membrane made with Hypalon® from DuPont**

Stevens EV is available in energy-efficient white and gray. Stevens CSPE is available in white only.

(Actual color may vary.)

▶ **Energy Efficient and Green**

Since the mid-1980s, we have been an industry-leading proponent of the benefits associated with white roofing systems. Our white roofing membranes have been shown to reflect heat and have a positive impact on energy costs. Stevens membranes meet the requirements of the Cool Roof Rating Council and California Title 24, and may qualify for U.S. Green Building Council points in the LEED® program. In addition to the white membrane, some Dow Colors (Buckskin, Light Slate Gray, Pewter, Desert Brown and Neon Blue) can also qualify for points in the LEED program.

▶ **Approved Attachment Methods**

Stevens membranes are versatile and can be installed by a variety of popular attachment methods, including:

- Mechanically Attached
- Fully Adhered
- Stone or Paver Ballasted
- Vented Roof Systems (VRS)



▶ **Available Dow Color Components**

Stevens membranes are reinforced and packaged in standard roll sizes of 76.5-in. wide x 100-ft. long (1.94 x 25.4 m), and 38.25-in. (.97 m) wide half-sheets packaged in random lengths. Matching unreinforced 55-mil (1.4 mm) material is available in all colors for flashing details and 45 mil (1.14 mm) material is available for wall flashings only.

Stevens Clear Cut-Edge Sealant is available for use with all colored membranes.

▶ **How to Order Dow Colored Membrane**

Limited quantities of Light Slate Gray and Buckskin are in-stock and available for immediate delivery. All other colors of Dow Colored membranes are subject to minimum order sizes. Contact your local Dow Roofing Systems representative for additional information on our color membranes and custom colors.

If you have any questions about Dow Colored membranes, call the Customer Service Department at 800/621-ROOF, ext. 1062 or 1004.

US Headquarters
Nine Sullivan Road
Holyoke, MA 01040-2800
Phone: 800-621-ROOF
or 413-533-8100
Fax: 413-552-1070



ROOFING SYSTEMS

International Sales
Phone: 1-413-552-1000
Fax: 1-413-552-1198

**Dow Roofing Systems is an
ISO 9001 Certified Facility.**

www.dowroofingsystems.com



**Innovative
Technology**
Since 1863

All statements herein are expressions of opinion, which by performance and testing are believed to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our products are made without any knowledge that such recommended uses may infringe any patent. No warranty, expressed or implied, other than that described in this brochure, is made or intended. USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission. Stevens EP is a trademark of Dow Roofing Systems. Stevens EV is a registered trademark of Dow Roofing Systems. Elvaloy is a registered trademark of DuPont. Hypalon is a registered trademark of DuPont Performance Elastomers. The Dow diamond is a registered trademark of The Dow Chemical Company.

DRSDS37 08/08 ©2008 Dow Roofing Systems

Printed in the USA