

# STEVENS *DeckGrip* *Reel-Fast* Collated Seam Plates



## ***The Latest Innovation for Mechanically Fastening Stevens EP™ and Stevens EV™ Membranes to Steel, Wood, and Structural Concrete Roof Decks.***

- Packaged 500 plates per reel with a handle to quickly and easily distribute plates along the seam.
- Dramatically saves labor to lay out plates.
- Reel-Fast plates are pre-spaced on either 6-in. (.150 m) or 12-in. (.305 m) centers which eliminates guesswork on the roof.
- Roof inspectors have endorsed the Reel-Fast concept as a product that conforms to good roofing practice.
- Patented EyeHook™\* plates will not puncture the membrane, providing improved wind uplift performance.
- Finding the high rib is much easier and more consistent.
- FM Global Approved - see table on back of page for details.



➤ Stevens Reel-Fast is designed for use with DeckGrip™ fasteners.

DeckGrip Fastener Data					
Part Number	Size (in./mm)	Usable Thread Length in./mm	Pcs/ Bucket	Bucket/ Skid	GW/ Bucket lbs.
2087038	1-1/4"/31.75 mm	Full	1000	60	12
2087039	2"/50.8 mm	1-3/4"/38.10 mm	1000	60	19
2087040	3"/76.2 mm	2-3/4"/69.85 mm	1000	60	29
2087041	4"/101.6 mm	2-3/4"/69.85 mm	1000	60	38
2087042	5"/127 mm	3-3/4"/95.25 mm	1000	40	47
2087043	6"/150 mm	3-3/4"/95.25 mm	500	60	29
2087044	7"/178 mm	3-3/4"/95.25 mm	500	60	33
2087045	8"/203 mm	3-3/4"/95.25 mm	500	60	38
2087046	*10"/254 mm	3-3/4"/95.25 mm	500	15	47
2087047	*12"/305 mm	3-3/4"/95.25 mm	500	15	56
2087048	**14"/356 mm	3-3/4"/95.25 mm	**500	15	65
2087049	**16"/406 mm	3-3/4"/95.25 mm	**250	15	38

\*Limited Quantity-packed in box/\*\*Special Order

Stevens Factory Mutual Approvals with DeckGrip Fasteners and Plates		
Membrane/Row Spacing	Fastener Spacing O.C.	FMG Approval
Stevens EP 71"/1.803 m	12"/.305 m	1-90
Stevens EP 71"/1.803 m	6"/.150 m	1-135
Stevens EP 120"/3.048 m	12"/.305 m	1-75
Stevens EP 120"/3.048 m	6"/.150 m	1-105
Stevens EP 47"/1.194 m	6"/.150 m	1-195
Stevens EV 71"/1.803 m	12"/.305 m	1-90
Stevens EV 71"/1.803 m	6"/.150 m	1-135
Stevens EV 47"/1.194 m	6"/.150 m	1-195

Note: approvals with FMG approved steel or concrete decks.

Part No.	Description	Weight/Reel
2087131	2-3/8"/.060 m DeckGrip Seam Plates 12-in.(.305 m) o.c.	25 lbs. (11kg)/reel
2087138	2-3/8"/.060 m DeckGrip Seam Plates 6-in. (.150 m) o.c.	25 lbs. (11kg)/reel

\*Product is packaged 2 reels per box.

\*EyeHook is trademark of ITW Buildex



[www.stevensroofing.com](http://www.stevensroofing.com)

**US Headquarters**  
 Nine Sullivan Road  
 Holyoke, MA 01040-2800  
 Phone: 800-621-ROOF  
 or 413-533-8100  
 Fax: 413-552-1070  
 E-mail: [info@stvroof.com](mailto:info@stvroof.com)

**International Sales**  
 Phone: 1-413-552-1000  
 Fax: 1-413-552-1198  
 E-mail: [international@stvroof.com](mailto:international@stvroof.com)

**Stevens Roofing Systems**  
 is an ISO 9001:2000  
 Certified Company.

Innovative  
 Technology  
 Since 1863

All statements herein are expressions of opinion, which by performance and testing are believed to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our products are made without any knowledge that such recommended uses may infringe any patent. No warranty, express or implied, other than that described in this brochure, is made or intended. 01/06 © 2006 Stevens Roofing Systems.