



# PRODUCT SPECIFICATION DATA SHEET

## Stevens SW Fastener & Plate Kits

### General Description

The Stevens SW Fastener features a double-edge drill point, a deep buttress single lead thread, and is used in conjunction with a specially designed metal plate called the Stevens SW plate. The Stevens SW fastener and SW plate are the only parts approved for the FM 1-90 rating for 10-foot (3.05 m) wide Stevens EP membrane fastened at 12-inches (305 m) on center in 22 gauge FM approved steel decks. These parts are not interchangeable with any other Stevens plates or fasteners, and cannot be used for any other system or approval.

### Technical Specifications

**Color:** Blue

**Thread Diameter:** 0.320 (8.128 mm)

**Head Diameter:** 0.500 (12.7 mm)

**Head Style:** #3 Phillips

**Attachment Applications:** 22 ga. steel

**Coating:** CR-10\*

**Lengths Available:** 2-, 3-, 4-, 5-, 6-, 7-, 8-inches. (.051, .076, .102, .127, .152, .178, .203 m)

**Plate:** 2 3/8-in. (.060 m) barbed metal seam plate.

\*CR-10 corrosion resistant coating exhibits less than 15% red rust after 30 Kesternich cycles. CR-10 coating exceeds Factory Mutual Approval Standard 4470.

### Packaging

Stevens SW Fasteners and plates are packaged 250 Fasteners and 250 Plates per bucket.

Fastener Length	Thread Length	Fast./Bucket	Plates/Bucket	Weight/Bucket	Bucket/Skid
2-in.	1.75-in.	250	250	22 lbs.	48 lbs.
3-in.	2.75-in.	250	250	25 lbs.	48 lbs.
4-in.	3-in.	250	250	29 lbs.	48 lbs.
5-in.	3-in.	250	250	32 lbs.	48 lbs.
6-in.	4-in.	250	250	36 lbs.	48 lbs.
7-in.	4-in.	250	250	39 lbs.	48 lbs.
8-in.	4-in.	250	250	43 lbs.	32 lbs.